

# NTD2003



Filter shaker system



Multi-purpose cyclonic inlet allows for 38, 56 and 76mm accessories.

## Bigger is quite often better for many industrial applications providing a true workhorse whatever the situation.

The combination of Structofoam and stainless steel is a standard very close to our engineering hearts and this is never more obvious than in our classic NTD-2003 industrial model.

Here you have a big capacity machine. A powerful Structofoam TwinFlo two motor power head, giant “shake free” filter system, stainless steel container and heavy duty transit chassis. Designed to perform well and give good results – year in year out.

The 2003 model operates on a cyclonic separation basis and is fitted as standard with our universal aluminium cyclonic entry adaptor which permits the selection of accessories in 38mm (1½”), 51mm (2”) and 76mm (3”) allowing the machine to be used in many varied applications. Be it builder’s rubble, a chicken house or a textile mill, the 2003 model will give you good, long and reliable service.



Removable steel chassis



NTD2003

### Kit BA5 - 607167



Kit BA5 supplied with both NTD750 and NTD2003 as standard.

Model	NTD2003-2
Rated motor power (W)	960 x 2
Motor (direct airflow / bypass)	Bypass
Motor only airflow L/sec	96
Max suction height mm H <sub>2</sub> O	2400
Capacity L	60
Filter type	PermaTex + FibraTex
Bag + primary filtration level at 0.5 microns	48.3%
Bag + primary filtration level at 0.3 microns	24.5%
Bag + primary filtration level at 0.2 microns	18.9%
Filter bag type	HepaFlo 6BH
Filter bag layers	3
Micro HEPA cartridge fitted	No
To IEC 60704-2-1 weighted sound dB(A)	82.2 Single Speed
Cable length m	10.0
Cleaning range m	26.8
Hose length m	4
Tool head width mm	400
Approx weight machine only Kg	30.2
Machine dimensions WxLxH	560x660x1145mm
Power outlet Socket	N/A
Kit	BA5