



420BU UHS Propane Burnisher

34% more fuel efficient and 40% fewer oil changes
than the other national brands.

Reduces maintenance and operating costs.

- 1 SAFR to keep emissions low even when the air filter is dirty.
- 2 12 volt battery start.
- 3 Optional CentriVac™ dust control and EcoSense™ emissions monitoring systems.
- 4 RokBak™ action allows for quick and simple pad change.
- 5 Catalytic muffler exceeds EPA and CARB minimum requirements.
- 6 Easy access filters for quick and easy cleaning.
- 7 Triple anchor adjustable welded handle for long lasting maneuverability.
- 8 Soft tread 2" (5 cm) adjustable wheels for smooth operation and tool free pad pressure adjustment.
- 9 Integral metal skirt reduces dust and protects building occupants and furnishings.
- 10 "Hot @ 4 o'clock" setup reduces torque for true and straight operation.
- 11 Electric clutch standard on all models.
- 12 Lo-Torq Deck™ to reduce operator side torque and fatigue.



Featuring an 18 HP 603 cc engine from:

Kawasaki
Engines

TECHNICAL DATA



	420BU21	420BU24	420BU28	420BU40
Performance	25,000 ft²/hr. (2300 m²/hr.)	28,000 ft²/hr. (2600 m²/hr.)	34,000 ft²/hr. (3160 m²/hr.)	50,000 ft²/hr. (4600 m²/hr.)
Pad Sizes	21 in (53 cm)	24 in (61 cm)	28 in (71 cm)	2 x 21 in (2 x 53 cm)
Pad Speeds	2000 rpm	1800 rpm	1700 rpm	1850 rpm
Noise Level	< 89 db(A)	< 89 db(A)	< 89 db(A)	< 89 db(A)
Width	24.5 in (62 cm)	27.5 in (70 cm)	31.5 in (80 cm)	46.5 in (118 cm)
Length	56 in (142 cm)	58.5 in (149 cm)	61.5 in (156 cm)	61.75 in (157 cm)
Weight	215 lb (97 kg)	221 lb (100 kg)	234 lb (106 kg)	340 lb (154 kg)
Warranty	Engine: Parts & Labor - 2 yrs* Machine: Parts & Labor - 1 yr* *Excludes wear and maintenance items			

AVAILABLE MODELS

CSA listed, CARB/EPA certified, CE approved



The 420BU is available with the following features in 21, 24, 28 and 40 inch widths
Options: Battery Start, Steel Tank, Clutch, EcoSense™, Vacuum

Distributed By:



Proquip NZ Ltd
t: 0800 277 678
e: sales@proquipnz.co.nz
w: www.proquipnz.co.nz

