



We help you shine.™

## EnviroStar Green™

ALL PURPOSE NEUTRALIZER

PROQUIP NZ LTD - 0800 277 678 - [www.proquipnz.co.nz](http://www.proquipnz.co.nz)



**EnviroStar Green All Purpose Neutralizer** is a concentrated “green” neutralizing solution that is effective on resilient tile and all types of stone flooring. It increases adhesion of coatings to floors where alkalinity is a problem.

## DIRECTIONS

Read all directions and Safety Data Sheets (SDS) before using.

### NEUTRALIZING FLOOR AFTER STRIPPING

1. Dilute product at 1:10 (13 US oz per gallon of water or 500 ml per 5 liters of water).
2. Apply with mop or automatic scrubber to neutralize hard floors.
3. Allow to soak for 10 minutes, rinse with water and allow to dry thoroughly before applying sealer and/or coating. To neutralize vinyl floors, dilute at 1:64 (2 US oz per gallon of water or 80 ml per 5 liters of water).

### REMOVING SALT FILMS


1. Clean floors to remove soil residues.
2. Mix product per the following dilutions: Removal of light to moderate winter salt films: 1:128 (1 US oz per gallon or 40 ml per 5 liters of water) in mop bucket or automatic scrubber  
Removal of heavy winter salt films: 1:64 (2 US oz per gallon of water or 80 ml per 5 liters of water).
3. Pick up solution and allow floor to dry thoroughly before burnishing.

Distributed By:



Proquip NZ Ltd  
t: 0800 277 678  
e: [sales@proquipnz.co.nz](mailto:sales@proquipnz.co.nz)  
w: [www.proquipnz.co.nz](http://www.proquipnz.co.nz)

## SURFACES



VCT

HARD FLOOR SURFACES

## TECHNICAL DATA

|                               |                                 |
|-------------------------------|---------------------------------|
| <b>Description</b>            | All purpose neutralizer         |
| <b>Appearance</b>             | Clear, colorless liquid         |
| <b>pH</b>                     | 2.2 (as supplied)               |
|                               | ASTM E70-07                     |
| <b>Viscosity (Brookfield)</b> | <10 centipoise                  |
|                               | @ 68°F (20°C)                   |
| <b>Fragrance</b>              | None added                      |
| <b>Shelf Life</b>             | 2 years                         |
|                               | ASTM D1791-93 (2008)            |
| <b>Density</b>                | 8.7 lb/gal @ 68°F               |
|                               | ASTM D1475-98 (2008)            |
|                               | 1.05 kg/L @ 20°C                |
| <b>VOC</b>                    | 0.08% (as supplied)             |
|                               | 40 CFR Part 59 Subpart C        |
|                               | <0.01 (1:10)                    |
|                               | <0.01 (1:64)                    |
| <b>Container</b>              | 1.06 US gal/4 L (MPE packaging) |

## PRODUCT INFO

|                         |              |
|-------------------------|--------------|
| <b>Product Code</b>     | 338MPE       |
| <b>Volume</b>           | 4 liters     |
| <b>Shipping Package</b> | 4 x 4 liters |
| <b>Pallet Quantity</b>  | 48           |

CARB compliant



CERTIFIED FLOOR CARE PRODUCT  
CCD-147



RECOGNIZED FOR SAFER CHEMISTRY  
[WWW.EPA.GOV/DFE](http://WWW.EPA.GOV/DFE)