



We help you shine.™



ECLIPSE™ HD
HEAVY DUTY DEGREASER

PROQUIP NZ LTD - 0800 277 678 - www.proquipnz.co.nz



Eclipse HD is a heavy duty degreaser cleaner that rapidly removes the most stubborn greasy soils.

DIRECTIONS

Read all directions and Safety Data Sheets (SDS) before using.

GENERAL DEGREASING

- Mix degreaser with water according to the following dilution: Light Degreasing–1:64 2 US oz per gal water (16 ml per 1 liter water)
Medium Degreasing–1:32 4 US oz per gal water (31 ml per 1 liter water)
Heavy Degreasing–1:8 16 US oz per gallon water (125 ml per 1 liter water)
Very Heavy Degreasing of food processing equipment and surfaces, machines and automotive shop areas–1:4 32 US oz per gallon water (250 ml per 1 liter water).
- Apply to surface. Allow a contact time of 5 minutes.
- Rinse with clean water or wipe with clean mop or sponge.

DEEP SCRUB CLEANING OF FLOOR

- Mix degreaser with water according to the following dilution: Moderate Soiling–1:32 4 US oz per gal water (31 ml per 1 liter water)
Heavy Soiling - 1:8 16 US oz per gallon water (125 ml per 1 liter water)
- Apply to surface. Allow a contact time of 5 minutes.
- After deep scrubbing and rinsing, allow floor to dry thoroughly before recoating.


AQUAPHYLL:

- Apply diluted solution to surface by spray, mop, brush, cloth, sponge, automatic scrubber or soak tank. Test for surface compatibility in an inconspicuous area before general use.
- Allow sufficient contact time for the solution to work properly. Agitate if necessary.
- Rinse thoroughly with clean water. Food contact surfaces must be rinsed thoroughly with potable water and then sanitized.

SDS sheets available for download at pioneereclipse.com.

396_PDS 06/2016

SURFACES



ALL WASHABLE SURFACES

TECHNICAL DATA

Description	Industrial strength degreaser
Appearance	Clear dark purple liquid
pH ASTM E70-07	12.5 (as supplied)
Fragrance	Sassafras
Viscosity (Brookfield) @ 68°F (20°C)	<10 centipoise
Freeze/Thaw ASTM D3209-93 (2008)	Passes 3 cycles
Shelf Life ASTM D1791-93 (2008)	1 year
Flash Point ASTM D56-05 (2010)	>200°F (93°C)
Density ASTM D1475-98 (2008)	8.9 lb/gal @ 68°F 1.07 kg/L @ 20°C
VOC 40 CFR Part 59 Subpart C	5% (as supplied) 1.04% (1:4 dilution) 0.58% (1:8 dilution) 0.16% (1:32 dilution) 0.08% (1:64 dilution)
Container	2.50 US gal/9.5 L (FS packaging) 1.06 US gal/4 L (MP packaging) 1.06 US gal/4 L (MPE packaging) 0.53 US gal/2 L (DTC packaging)

PRODUCT INFO

Product Code	396FS	396MP	396MPE	396DTC
Volume	2.50 US gallons	1.06 US gallons	4 liters	0.53 US gallons
Shipping Package	2 x 2.5 gallons	4 x 1.06 gallons	4 x 4 liters	4 x 0.53 gallons
Pallet Quantity	48	48	48	88

Distributed By:



Proquip NZ Ltd
t: 0800 277 678
e: sales@proquipnz.co.nz
w: www.proquipnz.co.nz

