

# SAFETY DATA SHEET

According to HSNO Hazardous Substances (Safety Data Sheets) Notice 2017

### Section 1. Identification of the material and the supplier

Product: Eclipse Hard Floor Sealer
Product Use: Floor finish – Ready to Use

Product intended for commercial and industrial use only.

Restriction of Use: Refer to Section 15

New Zealand Supplier: **Proquip NZ Ltd**Address: 47 Fitzherbert Street
Petone, Wellington

Telephone: 0800 277 678

Emergency No: 0800 764 766 (National Poison Centre)

Date of SDS Preparation: 2 October 2020

### Section 2. Hazards Identification

Not classified as hazardous according to Regulation (EC) No. 1272/2008 which meets New Zealand jurisdiction criteria as per EPA Hazardous Substances (Classification) Notice 2017.

# Section 3. Composition / Information on Hazardous Ingredients

Ingredients	Wt%	CAS NUMBER.
propylene glycol monobutyl ether	1-5	5131-66-8
(2-methoxymethylethoxy)-propanol	1-5	34590-94-8

### Section 4. First Aid Measures

### Routes of Exposure:

If in Eyes Rinse with plenty of water. If irritation develops and persists, seek medical

attention.

If on Skin Wash with plenty of soap and water. If skin irritation occurs: get medical

advice.

If Swallowed Do not induce vomiting. Wash out mouth thoroughly with water. Never

give anything to the mouth of an unconscious person. Seek medical

attention if needed.

If Inhaled Remove person to fresh air. Remove contaminated clothing and loosen

remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Apply artificial respiration if not breathing. Get medical advice if breathing becomes

difficult.

### Most important symptoms and effects, both acute and delayed

Symptoms:

Ingestion:None expected under normal use.Inhalation:None expected under normal use.Skin:None expected under normal use.Eye:None expected under normal use.

# **Section 5.** Fire Fighting Measures

Hazard Type	Non Flammable Liquid.			
Hazards from	Hazardous combustion products: CO, CO2			
products	During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include but not limited to the above mentioned substances.			
Suitable	In case of fire: use dry chemical, water spray, foam, carbon dioxide.			
Extinguishing media				
Precautions for	As in any fire, wear self-contained breathing apparatus and suitable			
firefighters and protective clothing including gloves and eye/face protection. Fire-				
special protective	otective fighters should wear clothing conforming to EN469 for chemical			
clothing	incidents. Materials can splatter above 100°C.			
HAZCHEM CODE	None allocated			

## Section 6. Accidental Release Measures

Put on personal protective equipment (see Section 8). Keep spectators away. Floors may be slippery; use care to avoid falling.

Keep spills and cleaning run-off out of sewers and open bodies of water.

Small spills: Absorb spill with inert material (e.g. sand, earth) and dispose of as waste material in accordance with local regulations.

Large spills. Neutralize spill area. Dike and contain spill with inert material (e.g. sand, earth). Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for disposal. Dispose of in accordance with Section 13.

# Section 7. Handling and Storage

## **Precautions for Handling:**

- Avoid contact with eyes and skin
- · Wash hands thoroughly after handling.
- Use only in well-ventilated areas
- Wear protective clothing as detailed in Section 8.

## **Precautions for Storage:**

- Store away from incompatible materials listed in Section 10.
- Storage temperature (Max. 60°C Min. 1°C)
- · Keep from freezing.
- Keep container sealed when not in use.
- Keep out of reach of children.

### **Section 8 Exposure Controls / Personal Protection**

# **WORKPLACE EXPOSURE STANDARDS (provided for guidance only)**

Substance	TWA ppm	mg/m³	STEL ppm mg/m³
Dipropylene glycol methyl ether (skin) [34590-94-8]	100	606	150 909

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Workplace Exposure Standards and Biological Exposure Indices NOV 2019 11<sup>TH</sup> EDITION.

### **Engineering Controls**

Use only with adequate ventilation. Use local ventilation and other engineering controls to maintain airborne contaminants below established and recommended exposure limits. If this product contains ingredients with exposure limits, monitoring may be required to determine the effectiveness of ventilation and other control measures.

# **Personal Protection Equipment**







Eyes	Safety eyewear is recommended, to avoid chemical splashes and mists. Safety glasses or goggles (EN166).			
Hands	Chemical resistant gloves are recommended (EN374).			
Skin	If major exposure is possible, wear suitable protection such as rubber boots, apron, etc.			
Respiratory	Respiratory protection should be worn when there is a potential of inadequate ventilation. If exposure limits are exceeded or symptoms are experienced, use an approved respirator with multi-purpose combination filter. (E.g EN 14387- ABEK)			
Hygiene Measure.	Handle in accordance with good industrial hygiene and safety practice.			

# Section 9 Physical and Chemical Properties

Appearance	Liquid	
Colour	milky white, opaque	
Odour	slight	
Odour Threshold	Not available	
pH	7.8 [Method: ASTM E 70]	
<b>Boiling Point</b>	Not available	
Melting Point	Not available	
Freezing Point	Not available	
Flash Point	>93°C [Method: Closed cup, ASTM D 56]	
Flammability	Non Flammable	
Upper and Lower	Not available	
Explosive Limits		
Vapour Pressure	Not available	
Relative Density	1.02 kg/l @ 20°C	
Water Solubility	Miscible in water	
Partition Coefficient:	Not available	
Auto-ignition	Not available	
Temperature		
Decomposition	Not available	
Temperature		
Viscosity	< 10 centipoise @ 20°C	
Particle Characteristics	Not available	
VOC	7.02%	
Evaporation Rate	Not available	

# Section 10. Stability and Reactivity

Stability of Substance	This product is stable under normal conditions.			
Possibility of hazardous	None known			
reactions				
Conditions to Avoid	Do not mix with other chemicals unless stated on the product label.			
Incompatible Materials	None known.			
<b>Hazardous Decomposition</b>	None known. Refer to Section 5.			
Products				

### **Acute Effects:**

Swallowed	Not triggered. ATE mix (oral): > 2000 mg/kg
Dermal	Not triggered. ATE mix (dermal): > 2000 mg/kg
Inhalation	Not triggered. ATE mix (inhalation):> 20 mg/l (4 hr/vapour)
Eye	Not applicable.
Skin	Not applicable.

# **Chronic Effects:**

Carcinogenicity	Not applicable.
Reproductive	Not applicable.
Toxicity	
Germ Cell	Not applicable.
Mutagenicity	
Aspiration	Not applicable.
STOT/SE	Not applicable.
STOT/RE	Not applicable.

Component	CAS#	LD50 Oral- Rat (mg/kg)	LD50 Dermal - Rabbit (mg/kg)	LC₅₀ Inhalation- Rat (mg/l)
propylene glycol monobutyl ether	5131-66-8	5660	> 2000	> 3.5

# **Section 12. Ecotoxicological Information**

This product is not hazardous to the environment.

Toxicity

Component	CAS#	LC50 - 96 hr	LC/EC50 - 48 hr	EC50 - 72 hr
propylene glycol monobutyl ether	5131-66-8	vertebrate, 560-1000 mg/ml	Daphnia magna, >1000 mg/l	algae, 560 mg/l

Persistence and degradability

Component	CAS#	Biodegradation
propylene glycol monobutyl ether	5131-66-8	Readily biodegradable

# **Bioaccumulation**

	CAS#	Partition coefficient	Bioconcentration
Component		n- octanol/water (LogKow)	factor
			(BCF)
propylene glycol monobutyl ether	5131-66-8	1.2	< 100

**Mobility in Soil** 

Component	CAS#	Soil Organic Carbon- Water Partitioning Coefficient (Koc)
propylene glycol monobutyl ether	5131-66-8	1.3 - 6.0

# **Section 13. Disposal Considerations**

### **Disposal Method:**

Triple rinse and dispose of according to Local Regulations.

Precautions or methods to avoid: None known

### Section 14 Transport Information

# This product is NOT classified as a Dangerous Good for transport in NZ; NZS 5433:2012

# Section 15 Regulatory Information

This substance is NOT classified hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

HSW (HS) Regulations 2017 and EPA Notices	Trigger Quantity	
Certified Handler	Not required	
Location Certificate	Not required	
Tracking Trigger Quantities	Not required	
Signage Trigger Quantities	Not required	
Emergency Response Plan	Not required	
Secondary Containment	Not required	
Restriction of Use	Only use for the intended purpose.	

# **Section 16** Other Information

Glossary

EC50 Median effective concentration.
EEL Environmental Exposure Limit.
EPA Environmental Protection Authority

HSNO Hazardous Substances and New Organisms.

HSW Health and Safety at Work.

LC<sub>50</sub> Lethal concentration that will kill 50% of the test organisms

inhaling or ingesting it.

LD<sub>50</sub> Lethal dose to kill 50% of test animals/organisms.

LEL Lower explosive level.

OSHA American Occupational Safety and Health Administration.

TEL Tolerable Exposure Limit.

TLV Threshold Limit Value-an exposure limit set by responsible

authority.

UEL Upper Explosive Level WES Workplace Exposure Limit

#### References:

- 1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
- 2. Workplace Exposure Standards and Biological Exposure Indices Nov 2017 edition.
- 3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
- 4. Transport of Dangerous goods on land NZS 5433:2012
- 5. HSW (Hazardous Substances) Regulations 2017

### Disclaimer

This document has been prepared by TCC (NZ) Ltd and serves as the suppliers Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to TCC (NZ) Ltd or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While TCC (NZ) have taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, TCC (NZ) Ltd accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact the New Zealand distributor, if further information is required.

Issue Date: 2 October 2020 Review Date: 2 October 2025

Product Name: Eclipse Hard Floor Sealer
Date of SDS: 2 October 2020

SDS Prepared by: Technical Compliance Consultants (NZ) Ltd
Tel: 64 9 475 5240 www.techcomp.co.nz