
TwinTec Vano Three Into One Does Go

A comfortable, driver friendly, 120-litre, front wheel drive machine with a fantastic turning radius, gets in and out of places other machines just won't go.

The TwinTec Vario "three in one" (3 in 1) design has proved itself to be almost the perfect balance between sound common sense engineering and innovative and truly functional technology.

Yes, one machine which can be set to 3 different working widths: 650, 750 and 850 and all at the flick of a simple selection lever. This doesn't even need tools - anybody can do it at any time. You want it wide -

you want it narrow - 30 seconds is all that it takes.



The unique arrangement of 3 independent scrubbing heads which, by virtue of a simple adjustment mechanism, can provide a choice of scrubbing widths which, with the addition of a selection of brushes and pads, can provide customised performance on almost any surface application.








As unique today as when it started - patented technology

- Vario 3 In 1 Brush System
 Simple adjustment mechanism provides
 a choice of scrubbing widths suitable for almost any surface.
- Easy Dosing Pre-sets
 Correct chemical dosing for every task.
- Complete Cleaning Control
 Operator has full control of cleaning
 speed, brush speed, water flow and chemical dosing.
- Simple Operator Control Soft touch dashboard control system.
- Easy Maintenance Easy access to batteries and fuses for service purposes and brush change is simple with the swing out brush cover.
- On Board Charger Simple and convenient, just plug and go. Fully sealed low maintenance Gel
- Small Turning Radius Means great cleaning even in tight
- Safety Features Emergency stop button, power off removable key, horn button and hazard warning light and built in reversing alarm are just a few of the many safety features included.
- Easy Maintenance Easy access to batteries and fuses for maintenance.





In many applications changing circumstances change specific needs, so with the Vario you can change the specification to suit your exact requirements. It's not only the working widths that can be changed; it's the full operating performance that is under the driver's complete control - cleaning speed, brush speed, water flow and chemical dosing, nothing left to chance.







Easy brush change



Model	Motor	Motor	Power		Ru	n Time	Drive	Speed	Speed	Gradient	
TTV678	3x24V 400W	24V 400W	6 x 12V (24V) = 8 x 12V (24V) = (Optiona	400Ahr		5 Hrs 5 Hrs	600W	7.0km/h	3.5km/h	11%	
Scrub Widths	Brush W Speed Cap			Water Flow Rate		Nuchen Mix	Gross \	Gross Weight (full)		Dimensions (HxLxW)	
650mm 750mm	50/100/ 150/200rp		L Optional 5L	4L/mir 3L/mir 2L/mir	n	25:1 50:1 75:1		/+620kgs /+684kgs		676x1054mm	